

Page 1/8

*

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2022

Version number 77 (replaces version 76)

Revision: 30.03.2022

1.1 Product identifier	
Trade name: MOTIP CUT & DRILL LUBRICANT 500 ML	
Article number: 090407 1.2 Relevant identified uses of the substance or mixture and uses advised No further relevant information available. Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, enter Product category Corrosion inhibitor Process category PROC7 Industrial spraying PROC11 Non industrial spraying Application of the substance / the mixture Lubricant	
1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: European Aerosols B.V.* Wolfraamweg 2 NL-8471 XC Wolvega The Netherlands Tel : +31 (0)561 694400 e-mail: sds-nl@european-aerosols.com	
*Formerly known as Motip Dupli B.V.	
<i>Further information obtainable from:</i> Department Product Safety 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h - 17:00h) UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111	
SECTION 2: Hazards identification	
2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008	
flame	
Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised contained	er: May burst if heated.
2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation Hazard pictograms	1.
Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation	1.
Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation	1.
Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation Hazard pictograms	1. (Contd. on page

Page 2/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2022

Version number 77 (replaces version 76)

Revision: 30.03.2022

Trade name: MOTIP CUT & DRILL LUBRICANT 500 ML

(Contd. of page 1) Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe spray. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents / container in accordance with regional regulations. · Additional information: Buildup of explosive mixtures possible without sufficient ventilation. · 2.3 Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

×

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-55-8 EINECS: 265-158-7 Index number: 649-468-00-3 Reg.nr.: 01-2119487077-29	Distillates (petroleum), hydrotreated light paraffinic 🚸 Asp. Tox. 1, H304	20-<25%
EC number: 918-481-9 Reg.nr.: 01-2119457273-39	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics Asp. Tox. 1, H304 EUH066	12.5-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	12.5-<20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas IA, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) Flam. Gas IA, H220 Press. Gas (Comp.), H280 the wording of the listed hazard phrases refer to section 16	5-<10%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

• After skin contact: Generally the product does not irritate the skin.

· After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

(Contd. on page 3)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2022

Version number 77 (*replaces version* 76)

Revision: 30.03.2022

Trade name: MOTIP CUT & DRILL LUBRICANT 500 ML

- \cdot 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 Keep away from ignition sources.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. No special measures required.
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

(Contd. of page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2022

Version number 77 (replaces version 76)

Revision: 30.03.2022

Trade name: MOTIP CUT & DRILL LUBRICANT 500 ML

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- · Hand protection Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye/face protection Not required.

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical p	roperties
· General Information	-
· Physical state	Aerosol
· Colour:	Light yellow
· Odour:	Mineral-oil-like
· Odour threshold:	Not determined.
• Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling	
range	Not applicable, as aerosol.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	0.6 Vol % (Hydrocarbons, C10-C13, n-alkanes,
	isoalkanes, cyclics, < 2% aromatics)
· Upper:	10.9 Vol % (74-98-6 propane)
· Flash point:	Not applicable, as aerosol.
· Ignition temperature:	>200 °C (>392 °F) (Hydrocarbons, C10-C13, n-
	alkanes, isoalkanes, cyclics, < 2% aromatics)
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625.2 mm Hg)
	(Contd. on pag

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2022

Version number 77 (replaces version 76)

Revision: 30.03.2022

Trade name: MOTIP CUT & DRILL LUBRICANT 500 ML

	(Contd. of page
Density and/or relative density	
Density at 20 °C (68 °F):	0.7 g/cm ³ (5.8 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
· Appearance:	
· Form:	Aerosol
Important information on protection of health environment, and on safety.	and
Explosive properties:	Not determined.
Solvent content:	Not determined.
• Solvent coment: • Organic solvents:	50.0 %
0	50.0 %
· VOC (EC)	
	367.5 g/l 50.00 %
VOC-EU%	0.0 %
Solids content:	0.0 %
· Change in condition	Net much entre
· Evaporation rate	Not applicable.
· Information with regard to physical hazard cla	
· Explosives	Void
Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
• Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
• Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammab	le
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
• Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

*

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

GB (Contd. on page 6) Page 6/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2022

Version number 77 (replaces version 76)

Revision: 30.03.2022

Trade name: MOTIP CUT & DRILL LUBRICANT 500 ML

(Contd. of page 5)

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity

· LD/LC50 values relevant for classification:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50	>5000 mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rab)

Inhalative LC50/4h >4951 mg/m3 (rat)

Skin corrosion/irritation No irritant effect.
 Serious eye damage/irritation No irritating effect.

• **Respiratory or skin sensitisation** No sensitising effects known.

 \cdot 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

· 14.1 UN number or ID number		
· ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
$\cdot ADR$	1950 AEROSOLS	

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2022

Version number 77 (replaces version 76)

Revision: 30.03.2022

Trade name: MOTIP CUT & DRILL LUBRICANT 500 ML

IMDC	(Contd. of pag
IMDG IATA	AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Gases.
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" cla 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk according to IM instruments	0 Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity Code: E0
Transport category	Not permitted as Excepted Quantity 2
Transport category Tunnel restriction code	2 D

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.06.2022

Version number 77 (replaces version 76)

Revision: 30.03.2022

Trade name: MOTIP CUT & DRILL LUBRICANT 500 ML

	(Contd. of page 7)
· IMDG	
\cdot Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: R&D legislation and regulatory advisor

- · Contact: e-mail: sds-nl@european-aerosols.com
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases – Category 1A

Flam. Gas IA: Flammable gases – Category IA Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Asp. Tox. 1: Aspiration hazard – Category 1

 \cdot * Data compared to the previous version altered.