



962P CONCRETE, STONE & BRICK ADHESIVE

Special adhesive foam designed for bonding brick, aerated block, stone, natural stone etc. construction elements at buildings.

FEATURES & BENEFITS

- A special product which is transforming with collapsing from foam form to gel adhesive form in a couple of seconds after application.
- One component, fast curing, easy to use adhesive foam.
- Bonding blocks and stones during construction works.
- Powerful adhesion to concrete and stone variations.
- Suitable to use at interior and exterior applications.
- Remarkable resistance to weather conditions.
- More economical, practical and easy to use.
- Minimum expansion during drying period.
- No more extra burden or weight to building.
- Usable at low temperature like +5 °C.
- It does not contain any propellant gases which are harmful to the ozone layer.



No More Mortar,
No More Water,
Dust nor Bother

APPLICATION AREAS

- Bonding structural blocks of non-bearing interior walls.
- For use where fixed, permanent positioning of stone or concrete products is desired.
- Usable on;
 - Concrete pavers/slabs,
 - Segmental retaining walls and columns,
 - Cast stone copings,
 - Landscape blocks and bricks,
 - Polystyrene foam board,
 - Cellular lightweight concrete elements,
 - Ornamental precast,
 - Natural & manufactured stone,
 - Brick, aerated block, cinder block, bims block, gypsum block and gypsum panel bonding.



INSTRUCTIONS

- Optimal can temperature is +20 °C.
- Optimal application temperature is in between +5°C and +30 °C.
- Shake the can well before use. Screw the can onto an applicator gun.
- The outflow of the foam can be regulated with the trigger and controlled with the adjustment screw on the back side of the gun.
- Always keep the can upside down during application.
- Surfaces must be clean and free of oil or dust.
- It can adhere to even slightly damp surfaces.
- Apply the foam in between stones and use a little bit force to fix the materials. A plastic head hammer can be used.
- The amount of the foam that will be used depends on the thickness and weight of the stone.
- For a better appearance it is not recommended to apply the foam to the edges and corners of the stone. At least 2 or 3 cm gap must be left on the edges and corners and the foam should be applied to inner sides of the stone.
- Fresh foam can be cleaned by Akfix Foam Cleaner. Cured foam can be cleaned barely mechanically.

RESTRICTIONS

- Storage above +30 °C and below +5 °C shortens shelf life.
- Should be stored and transported in vertical position.
- Should be kept in room temperature for at least 12 hours before the application.
- Cured foam will discolor if exposed to ultraviolet light.
- Paint or coat the cured foam for best results in outdoor applications.
- Dried foam can be wiped out by mechanical force.
- Lower temperatures decreases yield and curing time.

SAFETY

- Contains Diphenylmethane-4, 4'-Diisocyanate. Harmful by inhalation. Irritating to eyes, respiratory system and skin.
- Do not breathe spray/vapor. Use only in well-ventilated areas.
- Wear suitable protective clothing and gloves.
- Pressurized container. Keep away from direct sunlight and do not expose temperatures over 50 °C.
- Do not pierce or burn, even after use.
- Keep away from sources of ignition, no smoking.
- Keep out of the reach of children.

STORAGE AND SHELF LIFE

- Guaranteed storage time in unopened package is 12 months.



PROPERTIES

Basis	: Polyurethane Prepolymer
Curing System	: Moisture Cure
Tack-Free Time	: 5-8 min (ASTM C1620)
Cure-Time	: 24 hours
Foam Color	: Light Yellow
Metric yield	: 120 meters in (1.3 cm) bead
Shelf life	: 12 months
Fire Class of the Cured Foam	: B3 (DIN 4102-1)(EN 13501-1)
Shear Bond Strength	: >12 MPa
Temperature Resistance	: -40°C to +90°C
Application Temperature	: +5°C to +30°C

PACKAGING

Product	Volume	Package
Concrete, Stone & Brick Adhesive	750 mL	12

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.