

Technical specifications - Jabra Pro 900 Series



Product name	Jabra Pro 920	Jabra Pro 930	Jabra Pro 925	Jabra Pro 935
Packaging dimensions (L x W x H)	Mono master carton: 600 x 399 x 316mm Mono unit box: 185 x 138.5 x 67.5mm Duo master carton: 600 x 399 x 235mm Duo unit box: 190 x 191 x 65mm	Mono master carton: 600 x 399 x 316mm Mono unit box: 185 x 138.5 x 67.5mm Duo master carton: 600 x 399 x 235mm Duo unit box: 190 x 191 x 65mm	Master carton: 600 x 399 x 316mm Unit box: 185 x 138.5 x 67.5mm	Master carton: 600 x 399 x 316mm Unit box: 185 x 138.5 x 67.5mm
Main unit dimension (L x W x H)	Base: 118 x 76 x 29mm Mono headset: 131 x 50 x 18mm Duo headset: 165 x 165 x 30mm	Base: 118 x 76 x 29mm Mono headset: 131 x 50 x 18mm Duo headset: 165 x 165 x 30mm	Base: 118 x 76 x 29mm Headset: 131 x 50 x 18mm	Base: 118 x 76 x 29mm Headset: 131 x 50 x 18mm
Weight	Base: 177g Mono headset: 29g Duo headset: 80g	Base: 165g Mono headset: 29g Duo headset: 80g	Base: 177g Headset: 29g	Base: 165g Headset: 29g
What's in the box	1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. Flat cable	1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. USB cable	1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. Flat cable	1. Warning and Declaration 2. Quick start guide 3. Warranty 4. Web Setup leaflet 5. Headset 6. Base 7. Charger 8. USB cable
Integral battery	Yes	Yes	Yes	Yes
Charging time	180 min	180 min	180 min	180 min
Fast charge	50% charging in 50 min / 20% charging in 20 min	50% charging in 50 min / 20% charging in 20 min	50% charging in 50 min / 20% charging in 20 min	50% charging in 50 min / 20% charging in 20 min
AC power supply	Yes	Yes	Yes	Yes
Certifications	CE, CB, FCC, IC, NOM, NTC, EAC, PSB, ICASA, SIRIM, ACMA, NZ Telepermit, UL, TCO	CE, CB, FCC, IC, NOM, NTC, EAC, PSB, ICASA, SIRIM, ACMA, NZ Telepermit, UL, TCO	CE, FCC, IC, UL, SRRC, TELEC, EAC, NCC, IDA, RoHS, Reach, KCC, ETA, ACMA, EMC, SIRIM, NTC, DGPosTel	CE, FCC, IC, UL, SRRC, TELEC, EAC, NCC, IDA, RoHS, Reach, KCC, ETA, ACMA, EMC, SIRIM, NTC, DGPosTel
Warranty	North America: 1 year limited warranty Europe/APAC: 2 year limited warranty	North America: 1 year limited warranty Europe/APAC: 2 year limited warranty	North America: 1 year limited warranty Europe/APAC: 2 year limited warranty	North America: 1 year limited warranty Europe/APAC: 2 year limited warranty
Bluetooth® device	N/A	N/A	Yes	Yes
Bluetooth® wireless technology	N/A	N/A	Bluetooth® Class 1 (only on dual connectivity)	Bluetooth® Class 1 (only on dual connectivity)
Supported Bluetooth® modes	N/A	N/A	SCO, eSCO, Sniff mode	SCO, eSCO, Sniff mode
Supported Bluetooth® profiles	N/A	N/A	A2DP (v1.2), Handsfree profile (v1.6), headset profile (v1.2), AGHFP (v1.6)	A2DP (v1.2), handsfree profile (v1.6), headset profile (v1.2), AGHFP (v1.6)
Bluetooth® compliance	N/A	N/A	Yes	Yes
Pairing PIN	N/A	N/A	Bluetooth®: 0000	Bluetooth®: 0000
Security	DSAA + DSC	DSAA + DSC	Authentication and encryption (Bluetooth® standard)	Authentication and encryption (Bluetooth® standard)
DECT Device	Yes	Yes	N/A	N/A
NFC	N/A	N/A	Yes (only on dual connectivity)	Yes (only on dual connectivity)
Operating range	Up to 120m/395ft	Up to 120m/395ft	Up to 100m/330ft	Up to 100m/330ft
Headset bandwidth	Narrowband and wideband	Narrowband and wideband	Narrowband and wideband	Wideband only
Connection (mini jack, USB, etc.)	RJ-9 for handset, RJ-9 for phone body, RJ-45 for AUX	Mini USB	Mini USB, RJ-9 for handset, RJ-9 for phone body, RJ-45 for AUX	Mini USB
Talk time	Up to 8 hours	Up to 8 hours	Up to 12 hours	Up to 12 hours
Standby time	Up to 33 hours	Up to 33 hours	Up to 7 days	Up to 7 days

Technical specifications - Jabra Pro 900 Series



Product name	Jabra Pro 920	Jabra Pro 930	Jabra Pro 925	Jabra Pro 935
Speaker Size	Mono: Ø 28 x 5.9mm Duo: Ø 23 x 6.2mm	Mono: Ø 28 x 5.9mm Duo: Ø 23 x 6.2mm	Ø 28 x 5.9mm	Ø 28 x 5.9mm
Speaker sensitivity	91±3dB (60mV at 1000Hz)	91±3dB (60mV at 1000Hz)	91±3dB (60mV at 1000Hz)	91±3dB (60mV at 1000Hz)
Speaker impedance	Mono: 32±4.8Ω (at 1000Hz) Duo: 64±1.5% Ohm at 1000Hz	Mono: 32±4.8Ω (at 1000Hz) Duo: 64±1.5% Ohm at 1000Hz	32±4.8Ω (at 1000Hz)	32±4.8Ω (at 1000Hz)
Speaker frequency range	Mono: 150Hz to 7 kHz (at output S.P.L.-10dB) Duo: 180Hz to 7 kHz	Mono: 150Hz to 7 kHz (at output S.P.L.-10dB) Duo: 180Hz to 7 kHz	150Hz to 7 kHz (at output S.P.L.-10dB)	150Hz to 7 kHz (at output S.P.L.-10dB)
Microphone type	Uni-directional microphone	Uni-directional microphone	Uni-directional microphone	Uni-directional microphone
Microphone sensitivity	-30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa)	-30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa)	-30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa)	-30 ± 2dB (f=1kHz, Pin=1Pa, OdB=1V/Pa)
Microphone frequency range	100Hz to 10kHz	100Hz to 10kHz	100Hz to 10kHz	100Hz to 10kHz

Additional information - Jabra Pro 900 Series

Product name	Jabra Pro 920	Jabra Pro 930	Jabra Pro 925	Jabra Pro 935
USB cord length	N/A	1.5m	N/A	1.5m
Operating temperature	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)	0°C to 40°C (32°F to 104°F)
Storage temperature	-20°C to 45°C (-4°F to 113°F)	-20°C to 45°C (-4°F to 113°F)	-20°C to 45°C (-4°F to 113°F)	-20°C to 45°C (-4°F to 113°F)
Power consumption	7.5V/650mA	7.5V/650mA	7.5V/650mA	7.5V/650mA
Current consumption microphone	70 to 150 uA	70 to 150 uA	70 to 150 uA	70 to 150 uA
Charging plug dimensions	Ø 2.35mm	Ø 2.35mm	Ø 2.35mm	Ø 2.35mm
Material used	Polycarbonate/Akrylonitril-butadien-styren (PC/ABS): CYCOLOY C1200HF, GY6A288 Thermoplastic Polyurethanes - TPU: Desmopan 445 Acetal (POM) Copolymer: POM Tepcon M90 Thermoplastic acetal homopoly: DELRIN 500 P Polybutylene Terephthalate (PBT): PBT S600F20 Thermoplastic Elastomer (TPE): TPE Hytrel 4069 Thermoplastic Elastomer (TPE): TPE Hytrel 3548 Polypropylene (PP): AV161 Thermoplastic vulcanizates (TPVs): Santoprene TPV 201-87 Silicone rubber: KE-931TU Fiber reinforced Polycarbonate: KLX FRPC-1860B-HY			
Features	Crystal clear sound, HD Voice – Wideband Audio, Jabra Software Applications (Pro 930 & Pro 935), Noise canceling microphone, PeakStop™, Remote Asset Management (Pro 930 & Pro 935), Remote Call Control, SafeTone™, Talk in comfort, up to 120 Meter/395ft, wireless freedom (Pro 920 & 930) up to 100 Meter/330ft, wireless freedom (Pro 925 & 935), 8-12 hour battery life, UC Plug-and-Play (Pro 935 & 930)			
Software application	Jabra Direct - enables Remote Call Control over most softphones/Jabra Xpress™ - remote mass deployment and management of Jabra USB audio devices			

SKU number	Description	Technology	EAN
920-25-508-101	Jabra Pro 920, EMEA	1.88-1.9 GHz EU standard DECT	5706991013566
920-25-508-102	Jabra Pro 920, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991013573
920-25-508-103	Jabra Pro 920, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991013580
920-29-508-101	Jabra Pro 920 Duo, EMEA	1.88-1.9 GHz EU standard DECT	5706991018318
920-29-508-102	Jabra Pro 920 Duo, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991018325
920-29-508-103	Jabra Pro 920 Duo, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991018332
920-65-508-105	Jabra Pro 920, NA	1.92-1.93 GHz US DECT 6.0	5706991013597
920-69-508-105	Jabra Pro 920 Duo, NA	1.92-1.93 GHz US DECT 6.0	5706991018349
930-25-503-101	Jabra Pro 930 MS, EMEA	1.88-1.9 GHz EU standard DECT	5706991013603
930-25-503-102	Jabra Pro 930 MS, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991013610
930-25-503-103	Jabra Pro 930 MS, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991013627
930-25-509-101	Jabra Pro 930, EMEA	1.88-1.9 GHz EU standard DECT	5706991013634
930-25-509-102	Jabra Pro 930, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991013641
930-25-509-103	Jabra Pro 930, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991013658
930-29-503-101	Jabra Pro 930 Duo MS, EMEA	1.88-1.9 GHz EU standard DECT	5706991018356
930-29-503-102	Jabra Pro 930 Duo MS, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991018363
930-29-503-103	Jabra Pro 930 Duo MS, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991018370
930-29-509-101	Jabra Pro 930 Duo, EMEA	1.88-1.9 GHz EU standard DECT	5706991018387
930-29-509-102	Jabra Pro 930 Duo, UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991018394
930-29-509-103	Jabra Pro 930 Duo, AU/NZ	1.88-1.9 GHz EU standard DECT	5706991018400
930-65-503-105	Jabra Pro 930 MS, NA	1.92-1.93 GHz US DECT 6.0	5706991013665
930-65-509-105	Jabra Pro 930, NA	1.92-1.93 GHz US DECT 6.0	5706991013672
930-69-503-105	Jabra Pro 930 Duo MS, NA	1.92-1.93 GHz US DECT 6.0	5706991018417
930-69-509-105	Jabra Pro 930 Duo, NA	1.92-1.93 GHz US DECT 6.0	5706991018424
925-15-508-108	Jabra Pro 925, APAC	BT (2G4)	5706991020540
925-15-508-185	Jabra Pro 925, JPTW,TH,PH,VN,NA	BT (2G4)	5706991016642

SKU number	Description	Technology	EAN
925-15-508-201	Jabra Pro 925 BT, EMEA	BT (2G4)	5706991016659
925-15-508-202	Jabra Pro 925 BT, UK, HK, SG	BT (2G4)	5706991016666
925-15-508-205	Jabra Pro 925 BT, NA	BT (2G4)	5706991016680
925-15-508-208	Jabra pro 925 BT, APAC	BT (2G4)	5706991020557
935-15-503-108	Jabra Pro 935 MS, APAC	BT (2G4)	5706991020571
935-15-503-185	Jabra Pro 935 MS, JP,TW,TH,PH,VN,NA	BT (2G4)	5706991016727
935-15-503-201	Jabra Pro 935 MS, BT, EMEA	BT (2G4)	5706991016734
935-15-503-202	Jabra Pro 935 MS, BT, UK, HK, SG	BT (2G4)	5706991016741
935-15-503-205	Jabra Pro 935 MS, BT, NA	BT (2G4)	5706991016765
935-15-503-208	Jabra Pro 935 MS BT, APAC	BT (2G4)	5706991020595
935-15-509-108	Jabra Pro 935, APAC	BT (2G4)	5706991020564
935-15-509-185	Jabra Pro 935, JP,TW,TH,PH,VN,NA	BT (2G4)	5706991016802
935-15-509-201	Jabra Pro 935 BT, EMEA	BT (2G4)	5706991016819
935-15-509-202	Jabra Pro 935, BT, UK, HK, SG	BT (2G4)	5706991016826
935-15-509-205	Jabra Pro 935 BT, NA	BT (2G4)	5706991016840
935-15-509-208	Jabra Pro 935 UC BT, APAC	BT (2G4)	5706991020588